

Complementary Solutions

Labelling

Disposable Insertion Tool

For the termination of cabling components without soldering, wire stripping or the use of screws. Universally applicable for LSA-PLUS modules, Series 1 to 10, LSA-PLUS NT and RJ45 jacks with LSA-PLUS contacts.

The insertion tool produces a gas-tight contact; without the scissors mechanism it can be used to terminate wires with a conductor diameter range from 0.35mm to 0.9mm, with an outer diameter of 0.65mm to 2.6mm.

Service life > 100 terminations.



Disposable Insertion tool

Ordering Information

Description	Quantity	Product No.
Disposable Insertion tool	Each	6417 1 830-00

Cable Protection Rings

To be mounted at the rear/side of the backmount frame; cable entries (15mm diam.). For protection of insulation when cable bundles are fed through the backmount frame.



Cable Protection Ring

Ordering Information

Description	Quantity	Product No.
Cable Protection Ring	Each	6050 3 044-00

Edge Protection Strip

Product for worker safety for use in partially equipped backmount frames.

It is placed over unused backmount frame fingers.



Edge Protection Strip
Length 60mm

Ordering Information

Description	Quantity	Product No.
Edge Protection Strip Length 60mm	Each	6092 3 017-01
Edge Protection Strip Length 120mm	Each	6092 3 017-00